/ ANTENNA PRODUCT

OVERVIEW







At MVG, we design our antennas with outstanding performance in mind. It begins with a careful design process, alternating simulation and measurements. It extends to the use of the most advanced machining techniques and quality materials to achieve tight mechanical tolerances. That's why all our antenna characteristics are outstanding. And that's why we can guarantee the best electrical performance/operational bandwidth trade-off.

Antennas Designed for Outstanding Performance

The MVG antenna design team is an experienced multi-disciplinary group that considers all aspects of the antenna during the full development sequence based on a concurrent engineering approach. Our design processes, involving state-of-the-art numerical simulation and CAD tools, are continuously validated with prototyping and measurements, enabling tight performance optimization and absolute confidence in the final result.

MVG antennas are manufactured from quality materials and benefit from advanced numerical machining technology. All processes, from conception and design to manufacturing and final testing, are regulated by high quality standards. Our commitment to excellence is demonstrated by our certification as an ISO 9001:2008 compliant manufacturer and ISO 17025 for antenna test and calibration.

International Standards and Projects Meeting Future Technological Challenges

MVG is actively involved in the continued development of international standards in antenna measurements. Our experts participate in numerous European and national research programs as part of a team of key players in research and innovation. Several of these projects have been in cooperation with the French Centre National des Etudes Spatiales (CNES) and the European Space Agency (ESA).

A Complete Antenna Product Range


Our product portfolio includes antennas for measurement applications, high-power antennas, and antennas for telecommunications and navigation.

Antennas for Measurement Applications comprise both Reference Antennas (pp. 9-37) and Measurement Probes and Feeds (pp. 40-81). The first are ideally suited for calibration reference within antenna measurement systems thanks to their high reliability and repeatability. The latter are precision microwave sensors to collect the characteristics of the device under test for all antenna measurement ranges (Planar, Cylindrical and Spherical Near-field, Far-Field, Compact Antenna Test Range, quasi monostatic RCS measurements, etc.).

Antennas for High Power Applications (pp. 86-94) are specifically conceived to handle high input RF power with no degradation to the radiation parameters.


Telecommunication antennas (pp. 98-108) are targeted to telecom standards and protocols ranging from 50 MHz to 18 GHz.

Positioning antennas (pp. 112-128) encompass terminal antennas for GNSS receivers and for localization/safety applications.




Quick guide

CATEGORY	ANTENNA	APPLICATION			
Antennas for measurement applications REFERENCE ANTENNAS	Dual ridge horn	Gain reference for medium gain antennas; wideband probe for far-field test ranges; feeder for reflector antenn			
	Electric sleeve dipole	Gain/efficiency reference for omni-directional antennas; CTIA ripple test; chamber reflectivity evaluation			
	Magnetic dipole	Gain/efficiency reference for omni-directional antennas; CTIA ripple test; chamber reflectivity evaluation			
	Monopole	Gain reference for automotive antenna test ranges			
	• Monocone	Wideband gain reference for automotive antenna test ranges			
	Wideband dipoles	Wideband gain reference for omni-directional antennas; CTIA ripple test; chamber reflectivity evaluation; efficiency reference; measurement accuracy evaluation			
	Standard gain horn	Gain reference for high gain antennas			
3	Linear array reference antenna	Gain reference for base station antennas and cylindrical near-field systems			
	Parabolic reflector SR 40	Gain/pattern reference for high gain antennas; far-field antenna measurements			
	• mm-Wave Chip	Gain reference for micro-probed antenna measurements			
	VHF Wideband Low-Profile	Low profile reference for measurements in VHF frequencies			
	Open-ended waveguide	Near-field measurements from UHF to W band; calibration and polarization reference			
	Dual polarized open-ended waveguide with interchangeable aperture	Planar near-field measurement; calibration and polarization referen			
Antennas for measurement applications MEASUREMENT PROBES AND FEEDS	Dual polarized minimum scattering probe	Planar near-field measurement			
	Dual polarized probe	Far-field measurements; spherical near-field measurement; calibration and polarization reference			
	Low-frequency probe	Planar and spherical near-field low frequency measurements; Illumination of CATR systems			
	Open boundary quad-ridge horns	Low frequency PNF/CNF measurements; wideband antenna measurements in SNF and Compact Antenna Test Ranges; reflector feed for high gain applications			
	Compact range feed horn	Illumination of compact antenna test range systems; Illumination of reflector antennas; direct range illumination			
	CATR feed for cross-polar compensation	Feed for cross-polar reduction in non-compensated compact antenna test ranges			
,	Quad-ridge flared horn	Wideband illumination of compact antenna test range systems; wideband feed for reflector antennas			
	Diagonal horn	Gain reference for medium/high gain antennas; measurements in far-field test ranges; quasi-monostatic radar cross section (RCS) measurements			
	Closed boundary quad-ridge horn	Gain reference for medium/high gain antennas; wideband illumination of compact antenna test range systems; Quasi-bistatic radar cross-section measurements			
	Log periodic antenna	• Illumination of anechoic chambers; far-field antenna measurements			
	VHF Wideband Dual Polarized Probe	Dual polarized probe for spherical near-field measurements in VHF frequencies			



Quick guide


CATEGORY	ANTENNA	APPLICATION		
Antennas for High Power Applications	Omni-directional high power antenna	High power emission on cellular network frequencies		
	UWB discone antenna	High power ultra-wide band application		
7 100110110	High power medium gain wideband horn	Wideband transmitter; direction finding applications		
	High power log-periodic antenna	Wideband transmitter; direction finding applications		
	Wideband transmit airborne antenna	Air-to-ground high power emission applications		
Telecommunication	Planar antennas for integrated application	General transmitting and receiving applications at 24 GHz; radar and radio link point-to-point		
Antennas	Planar antennas for WLAN application	General transmitting and receiving applications from 2.1 to 5.8 GHz radar doppler and radio link point-to-point		
	Planar antennas for wireless communication application	General transmitting and receiving applications from 880 MHz to 5.875 GHz; point-to-point telecommunications		
	Omni-directional low power antenna	Data transmission base station for telecommunications		
	• UWB antenna	High speed data transmission for telecommunication applications		
	Unal circular polarized reflector leed	Illumination of reflector antennas; ground station transmitter; simultaneous TX/RX in dual circular polarization		
Positioning	GNSS antennas for embedded application	Positioning of equipment for land, aerospace and maritime applications		
Antennas	Professional GALILEO/GPS terminal antenna	Ground segment portable antenna for professional applications covering GALILEO E5, E6, L1 bands and GPS L5, L2, L1 bands		
000	GALILEO/GPS/GLONASS base station reference antenna	Reference applications covering GALILEO E5, E6, L1 bands, GPS L5, L2, L1 bands and GLONASS L2, L1 bands		
000	GALILEO/GPS base station reference antenna	Reference applications covering GALILEO E5, E6, L1 bands and GPS L5, L2, L1 bands		
	ARGOS Tx/Rx ultra compact terminal antenna	Bi-directional data transmission (activity, environmental or localization) for Argos 3 user applications (ships, shipping containers, etc.)		
	COSPAS-SARSAT ultra compact terminal antenna	Localization, safety and rescue applications		




Measurement probes and feeds

Introduction

MVG probes and feeds are dedicated microwave sensors to characterize a device under test. Antenna specifications are tailored to the specific measurement range and technique used, either based on Near-field or Far-field methods. Near-field methods have the advantage of requiring compact systems; the measurement distance is only a few wavelengths. Transformation is then used to determine the far-field, which can be implemented by means of an analog approach, as in CATR systems, or by means of a numerical approach. The latter requires the field to be sampled in a specific geometry (planar, cylindrical, spherical) in order for the field transformation to be applied. MVG measurement probes are conceived to approach the ideal physical constraints imposed by near-field and far-field measurement techniques, in order to obtain the most accurate characterization of the antenna under test.






A unique precision product

MVG measurement probes are the result of a unique combination of know-how in antenna measurement, antenna design, and manufacturing.

MVG measurement probes are conceived to approach the ideal physical constraints imposed by near-field and far-field measurement techniques, in order to obtain the most accurate characterization of the antenna under test. The probe design is supported by state-of-the-art electromagnetic simulation software and strengthened by the use of advanced numerical tools, specifically developed for MVG antenna measurement systems.

MVG measurement probes are manufactured in aluminum using high precision machining techniques in order to guarantee excellent repeatability and accurate electrical performance.



VHF Wideband Dual Polarized Probe


Wide bandwidth

Reducing the number of probes required to perform a wideband test has many advantages.

Probe interchanging during a wideband test will modify the measurement conditions over the frequency band under test. Conversely, a single wideband probe preserves the measurement accuracy and allows an uninterrupted sweep, therefore shortening the measurement time.

Dual linear polarization

The integrated orthomode junction allows simultaneous acquisition of the orthogonal field components, therefore speeding up the measurement process. Furthermore, MVG probes do not require complex positioners and have a minimum impact on the overall measurement accuracy since no mechanical rotation is required to change polarization.




Ultra wideband ortho-mode junction

New developments in probe technology and ortho-mode junctions (OMJ) have enabled near and far-field probes to reach a 1:4 bandwidth, while maintaining high performance standards similar to traditional narrow band probes.

L. J. Foged, A. Giacomini, S. Pivnenko, "Wide band dual polarized probes for near and farfield measurement systems", AMTA 2007, November 4-9, 2007 St. Louis, MO, USA. L. J. Foged, A. Giacomini, R. Morbidini, "Probe performance limitation due to excitation errors in external beam forming network", 33rd Annual Symposium of the Antenna Measurement Techniques Association, AMTA, October 2011, Englewood, Colorado, USA

Inverted quad-ridge circular waveguide

Traditional ortho-mode junctions in circular waveguide, based on balanced feeding, are realized by a pair of excitation pins per polarization, each pair fed by a 0°/180° hybrid coupler, and are able to provide excellent performance over a narrow bandwidth. The main drawback of such technology is the limit on the useable bandwidth due to the high sensitivity to excitation errors that cause higher order modes to arise and propagate. The inverted quad-ridge waveguide technology solves this problem. It is inherently wideband and can be fed by a balanced excitation layout. The result is a great improvement in terms of robustness to excitation errors, therefore providing an ultra broad operating bandwidth.




SATIMO Patent, 2010-02-11, Inventors: Foged Lars Jacob, Giacomini Andrea, Duchesne Luc, Publication number: US2010033264 (A1), FR2907601 (A1), WO2008049776 (A1), EP2092592 (A1), "Orthogonal-mode junction coupler with an ultra-broad operating bandwidth"

Auto-balanced ortho-mode junction

MVG has developed an innovative ortho-mode junction in a circular waveguide, providing excellent isolation between the polarizations and single mode excitation over 1:1.5 bandwidth, without the need of a feeding network based on 0°/180° hybrid couplers. This technology is derived from conventional ortho-mode junctions in circular waveguides, consisting of orthogonal feeding points that are offset along the axis of the coupler, and is aimed at solving the common drawbacks of traditional techology. In particular, conventional couplers have an asymmetry which leads to degradation of the modal purity due to the excitation of higher order modes. Furthermore, because of the close proximity between orthogonal feeding points, poor port-to-port decoupling can occur. In order to solve these drawbacks and provide single mode excitation, a capacitively coupled symmetrical structure, consisting of two C-shaped branches extending out from each side of the circular waveguide, has been introduced. Independent polarization short circuits allow the orthogonal feeding points to be well separated, thus greatly improving the port-to-port isolation.







SATIMO Patent, 2007-10-18, Inventors: Foged Lars Jacob, Giacomini Andrea, Publication number: US20100090779 (A1), US8125294 (B2), WO2008049778 (A1), WO2008049778 (A8) (A1), EP2092595 (A1), "Method of orthogonal-mode junction coupling with a medium to broad operating bandwidth, and coupler employing said method"

Main probe requirements in Antenna Measurement SPHERICAL NEAR-FIELD **FAR-FIELD PLANAR NEAR-FIELD Low Directivity Low/Mid Directivity High Directivity** · Radiation pattern dominated by first-order High on-axis polarization purity No sidelobes and no pattern nulls in the forward hemisphere spherical modes (allowing for first-order Low sidelobes • Equalized beamwidth (E/H-planes) Stable phase center with frequency probe correction) Low backscattering Low chamber illumination · High on-axis polarization purity

Which measurement probe or feed for which configuration?









FAR-FIELD

	Frequency Range			Dual Pol.	Main Characteristics
HIGH PRECISION OFFSET PARABOLIC REFLECTOR				х	High gain Stable phase center over frequency Excellent on-axis cross-polar discrimination
CLOSED BOUNDARY QUAD-RIDGE HORNS				Х	Stable phase center over frequency Excellent cross-polar discrimination and port-to-port isolation
DIAGONAL HORNS			х		High gain Equalized beamwidths Extremely low sidelobes
DUAL POLARIZED PROBES				х	High polarization purity Equalized beamwidths
LOG-PERIODIC ANTENNAS			x		Entry-level solution for FF measurements
	0.1 1 Fr	10 100 requency (GHz)			




COMPACT ANTENNA TEST RANGE





Custom probes



Quality Products and Services,

the Key to Customer Satisfaction

Quality Management System

MVG is an ISO 9001: 2008 certified manufacturer of antennas and measurement systems. This certification ensures that:

- Our products meet customer and applicable regulatory requirements
- Our processes aim at continuous improvement of customer satisfaction and conformity of our products to requirements.





2 Controlling the Chain of Suppliers

In its drive for excellence in antenna design, MVG has established a network of suppliers that meet our demanding requirements. Working with local suppliers, each specializing in a different material processing and/or manufacturing technique, allows us to regularly check and validate those processes and maintain the quality control we demand. We believe that the use of quality raw materials and advanced machining complemented by cost-controlled processes leads to superior products at an optimal price for our customers.

8 Regular Calibration of our Measurement Facilities

To guarantee our customers high reliability and measurement quality during the antenna design, optimization and acceptance process, our measurement facilities are regularly calibrated. Antennas are tested in our facilities in Atlanta, GA (USA), Paris and Brest (France), or Rome (Italy). The facility in Atlanta is a CTIA Authorized Test Lab and a2La accredited. The facility near Paris, has also received 3GPP test and calibration accreditation according to ISO 17025.







The scope of accreditation is location dependent and does not include the entire scope of MVG activities. Visit our credentials page on the MVG website for details.



4 Antenna Final Acceptance Test


Each antenna produced by MVG goes through meticulous quality control before it is shipped to customers. This involves Inspection, Analysis, Demonstration and Test (IADT) qualification methods. It is well-known that antenna S-parameters are very sensitive indicators of manufacturing flaws, and severe measures of repeatability. The RF response of antennas

manufactured by MVG is individually tested and compared with strict performance boundaries. The measured S-parameters data is supplied with each antenna. Depending on the specific antenna, additional verifications are conducted, such as metrological or RF testing, in order to verify full compliance with specification.

5 TYMEDA™ A Comprehensive Database of Antenna Performance Data

MVG antennas are supplied with TYMEDA™ performance data including uncertainty boundaries. The TYMEDATM TYpical MEasured DAta originates from the collection of a comprehensive database on antenna performance, built over the years through a very large number of measurements using different techniques and system configurations, enriched by measurements in accredited and independent calibration labs. This database is further reinforced by International Facilities Comparison Campaigns [RD1], [RD2], [RD3], [RD4], [RD5], [RD6], [RD7]. Refined and detailed state-of-the-art electromagnetic models, accounting for realistic materials and relevant manufacturing details and constraints, give further support to the collected measurement data. A statistical approach is then used to combine multiple measured datasets and simulated data, thus reducing measurement uncertainties and improving the dynamic range of the data. The reliability of this approach has been widely validated and draws its strength from the high manufacturing accuracy and repeatability of MVG antennas [RD8], [RD9], [RD10], [RD11]. TYMEDA™ is therefore an accurate and reliable estimator of the actual performance of an antenna.

- [RD1] L. J. Foged, P. Garreau, O. Breinbjerg, S. Pivnenko, M. Sierra-Castañer, J. Zackrisson, "Facility comparison and evaluation using dual ridge horn", AMTA 2005, Newport;
- [RD2] L.J. Foged, O. Breinbjerg, S. Pivnenko, G. Di Massa, C. Sabatier, "Antenna measurement facility comparison within the European Antenna Centre of Excellence", EuMC 2005, Paris;L.J. Foged, A. Giacomini, L. Scialacqua, R. Morbidini, J. Estrada, "Investigation of SGH performance and repeatability", AMTA 2010, Atlanta;
- [RD3] L. J. Foged, B. Bencivenga, L. Durand, O. Breinbjerg, S. Pivnenko, C. Sabatier, H. Ericsson, B. Svensson, A. Alexandridis, S. Burgos, M. Sierra-Castañer, J. Zackrisson, M. Boettcher, "Error calculation techniques and their application to the Antenna Measurement Facility Comparison within the European Antenna Centre of Excellence", EuCAP 2007, Edinburgh;
- [RD4] L.J. Foged, B. Bencivenga, O. Breinbjerg, S. Pivnenko, M. Sierra-Castañer, "Measurement facility comparisons within the european antenna centre of excellence", ISAP 2008, Taipei;
- [RD5] L.J. Foged, B. Bencivenga, L. Scialacqua, S. Pivnenko, O. Breinbjerg, M. Sierra-Castañer, P.C. Almena, E. Seguenot, C. Sabatier, M. Bottcher, E. Arnaud, T. Monediere, H. Garcia, D. Allenic, G. Hampton, A. Daya, "Facility comparison and evaluation using dual ridge horns", EuCAP 2009, Berlin;
- [RD6] L.J. Foged, M. Sierra-Castañer, L. Scialacqua, "Facility comparison campaigns within EurAAP", EuCAP 2011, Rome;
- [RD7] L. Scialacqua, F. Mioc, J. Zhang, L.J. Foged, M. Sierra-Castañer, "Antenna Measurement Intercomparison Campaigns in the framework of the European Association of Antennas and Propagation", ISAP 2013, Nanjing;
- [RD8] A. Giacomini, B. Bencivenga, L. Duchesne, L.J. Foged, "Determination of high accuracy performance data for dipole reference antennas", European AMTA conference 2006, Munich;
- [RD9] L.J. Foged, A. Giacomini, L. Scialacqua, R. Morbidini, N. Isman, "Comparative investigation of SGH performance prediction formulas, measurements and numerical modelling", EuCAP 2010, Barcelona;
- [RD10] L.J. Foged, A. Giacomini, L. Scialacqua, R. Morbidini, J. Estrada, "Investigation of SGH performance and repeatability", AMTA 2010, Atlanta;
- [RD11] L.J. Foged, A. Giacomini, L. Duchesne, E. Leroux, L. Sassi, J. Mollet, "Advanced modelling and measurements of wideband horn antennas", ANTEM 2005, Saint-Malo;



A global presence

Microwave Vision exports more than 90% of its production outside of France. The Group spans Europe, Asia and America through 20 locations in 10 countries.

MVG Industries

17 avenue de Norvège 91140 Villebon-sur-Yvette FRANCE

Tel: +33 (0)1 69 29 02 47

MVG - Corporate HQ

47, boulevard Saint Michel 75005 Paris FRANCE

Tel: +33 (0)1 75 77 58 50

MVG Industries Bretagne

Technopole Brest Iroise, Z.I. du Vernis, 225 rue Pierre Rivoalon, 29200 Brest FRANCE

Tel: +33 (0)2 98 05 13 34

Orbit/FR Germany

ORBIT/FR Germany J. S. Bach-Str. 11 85591 Vaterstetten GERMANY

Tel: +49 (0)810 699 6060

Orbit/FR Israel

1 Gesher Ha-Ets St., P.O. Box 12096, Emek Hefer Industrial Park, 38777-01 Emek Hefer

Tel: +972 74 713 0130

MVG Italy

Via Castelli Romani, 59 00040 Pomezia (Rome) ITALY

Tel: +39 06 89 99 53 11

Research and



MVG Sweden

P.O. Box 35 44121 Alingsas Gothenburg SWEDEN

Tel: +46 31 402 430

Rainford EMC Systems Limited

Unit 400, Haydock Lane, Haydock WA11 9TH UNITED KINGDOM

Tel: +44 (0)1 942 296 190

MVG Hong-Kong

Suite 702, 7th floor Cyberport 1 100 Cyberport Road Pok Fu Lam Hong Kong SAR CHINA

Tel: +85 229 896 128

MVG India

N° 414 Cunnigham Road Level 4 Prestige Centre Point, 560052 Bangalore INDIA

Tel: +91 70 22 98 12 16

Production site in Israel



MVG Japan

#101 Confort Musashi-Nakahara, 2-10-32, Shimokodanaka, Nakahara-ku, Kawasaki-city 211-0041 Kanagawa JAPAN

Tel: +81 44 948 9301

Orbit/FR's Corporate HQ

506 Prudential Road Horsham, PA 19044 UNITED STATES Tel: +1(215) 674 5100

MVG, Inc

2105 Barrett Park Dr., Suite 104 Kennesaw, GA 30144 UNITED STATES

Tel: +1 678 797 9172

AEMI

1320 Air Wing Road, suite 101 Otay Mesa, CA 92154 UNITED STATES

Tel: +1 (619) 449 9492

